Single Gas Clip



Single Gas Clip
Portable detector

Robust and maintenance-free gas detector for single gas detection

Single gas detection

Gas	Measuring Range	Alarm
H2S Hydrogen sulfide	0-100 ppm	5 ppm 10 ppm
CO Carbon monoxide	0-300 ppm	25 ppm 50 ppm
O2 Oxygen	0-30 vol %	19,5 % 23,5 %

2-way IR communication
Log download, bump test, and updates

User-defined setup
Alarm thresholds, calibration intervals, and self-test intervals can be adjusted and set by the user

Reliable and user-friendly

- Unmatched reliable sensor for H2S, CO, or O2
- Designed for use in all weather conditions
- Operated with a single button
- Real-time display (Single Gas Clip Plus)
- Compact and simple design
- Alarms indicated with light, vibrator, and horn (min. 95 dB)
- Automatic self-test
- Automatic log of the last 25 results

No maintenance costs

- Battery life: 2 years
- Warranty: 2 years, after which the detector is disposed of

Technical data

Size:	85,5 x 48 x 29 mm
Weight:	76 gram
IP rating:	IP 67
Certified:	ATEX Zone 0, 1, 2

geopal®
Bygmarken 19 • DK-3520 Farum
+45 4567 0600 • info@geopal.dk • www.geopal.dk

PENDING ITS-I 23ATEXQ36745 DBI reg. no 233.301 DIC444QMS