

Multi Gas Clip Simple



Simple and user-friendly

- Designed for use in all weather conditions
- Compact and simple design
- Ergonomic
- Real-time gas readings
- Alarm indicated with light, vibrator, and horn (min. 95 dB)
- Automatic self-test runs continuously during use
- Automatic log every second of the last 25 results

No maintenance costs

- Battery life: 2 years
- Warranty: 2 years, after which the detector is disposed of

Multi Gas Clip Simple Portable detector

Make gas detection simple!

Detection of up to 4 gases

Gas	Measuring range	Resolution
H2S Hydrogen sulfide	0-100 ppm	1 ppm
CO Carbon monoxide	0-500 ppm	1 ppm
O2 Oxygen	0-30 %	0,1 %
LEL Explosive gases	0-100 % LEL	0,1 %

2-year lifetime

No charging, calibration, or maintenance required

LEL sensor (IR)

Accurately detects in environments with high or limited oxygen
Immune to H2S and silicone vapors

User-defined setup

Alarm thresholds, calibration and bump-test intervals, language, etc., can be adjusted and set by the user

Calibration and service

Available at Geopal or at the customer's site

Technical data

Size: 120,65 x 69,85 x 31,75 mm
Weight: 220,20 gram
IP rating: IP 68
Certified: ATEX Zone 0, 1, 2

geopal®

Bygmarken 19 • DK-3520 Farum
+45 4567 0600 • info@geopal.dk • www.geopal.dk

EA 50110AE



PENDING



ITS-I 23ATEXQ36745



DBI reg. no 233.301



DIC444QMS