GasAlert BW Clip



Example: Honeywell GasAlert BW Clip for H_2S

Honeywell GasAlert BW Clip
Portable gas detector

The Honeywell GasAlert BW Clip is a maintenance-free single-gas detector available for H_2S, CO, O_2, and SO_2.

No calibration, no sensor or battery replacement, no charging. It features one-button operation, clear LED/audible/vibration alarms, and automatic logging of the last 35 events/bump tests.

Rugged and user-friendly

- 24 months of maintenance-free operation
- Designed for all-weather use
- One-button operation
- Compact, simple design
- LED/horn/vibration alarms
- Automatic self-test
- Auto-log of the last 35 gas events and bump tests

Technical data

Size	4,1 x 5,0 x 8,7 cm
Weight	92 gram
IP	IP 66/67
Certified	ATEX Zone 0, 1, 2

Single-gas measurement ranges

Gas	Measuring Range	Alarm
H_2S Hydrogen Sulphide	0-100 ppm	L: 10 ppm H: 15 ppm
CO Carbon Monoxide	0-300 ppm	L: 35 ppm H: 200 ppm
O_2 Oxygen	0-25,0 % vol.	L: 19,5 % H: 23,5 %
SO_2 Sulfur Dioxide	0-100 ppm	L: 5 ppm H: 10 ppm

Alarm Level Low / High
Alarm levels are user-configurable

geopal®
Bygmarken 19 • DK-3520 Farum
+45 4567 0600 • info@geopal.dk • www.geopal.dk

PENDING ITS-I 23ATEXQ36745 DBI reg. no 233.301 DIC444QMS