

Blackline Safety G8



Overview of all detectors

In Blackline Live, the responsible person has the option to, among other things:

- view the current location of employees
- monitor alarms in real time
- manage devices and groups
- monitor bump tests and calibration
- analyse incidents and exposures
- generate reports and documentation

Real-time display of measurement values from all detectors.

Technical data

Warranty:	2 years
IP rating:	IP67
Certified:	ATEX Zone 0, 1, 2
Battery life:	Up to 24 hours Charges in approx. 4 hours
Operating temperature:	-20 °C to +55 °C

Blackline Safety G8 Portable detector

Personal safety with direct communication

Blackline G8 combines gas detection, lone worker safety, GPS positioning and communication in one integrated solution.

Via the 4G network, data is shared in real time, allowing safety managers to respond quickly to alarms and gain an overview of employee status and location. In the event of an incident or emergency, relevant personnel can automatically receive notifications and access up-to-date information about the employee and the situation.

G8 can be configured for both lone working and gas detection and is available with replaceable cartridges for single-gas, multi-gas or pump versions for work in confined spaces.

Features include:

- Man-Down alert
- No-Motion alert
- Check-In function
- Emergency alert (SOS)
- GPS positioning
- Real-time alerts
- Gas detection of up to 5 gases

Detection of up to 5 gases

G8 supports more than 20 different sensor types and can be configured for a wide range of applications.

Examples of gases:

H2S	Hydrogen sulphide
LEL	Flammable gases
CO	Carbon monoxide
O2	Oxygen
CO2	Carbon dioxide
NH3	Ammonia
Cl2	Chlorine

Direct communication

Built-in Push-to-Talk (PTT) makes it possible to communicate directly between G8 devices.

geopal[®]

Bygmarken 19 • DK-3520 Farum
+45 4567 0600 • info@geopal.dk • www.geopal.dk

EA 50072AE



PENDING



ITS-1 23ATEXQ36745



DBI reg. no 233.301



DIC444QMS